|  | Title           | Teknipure C of C  |  |  |  |  |
|--|-----------------|-------------------|--|--|--|--|
|  | Document Number | FM-8.2.5.1        |  |  |  |  |
|  | Revision Date   | February 20, 2022 |  |  |  |  |

## **Certificate of Conformance**

Wiper Code: TC2PL1-99G

LOT No: 527238-210423

| Basis Weight (g/m²)<br>ASTM D3776 |                        |                        | Thickness (mm) ASTM D1777-96 |                         |                         |                        | Orbital Shake Test for Particles<br>IEST-RP-CC004.3 Section 6.1.4<br>(x10 <sup>6</sup> particle/m <sup>2</sup> ) |                    |                    | Fiber/Particles IEST-RP-CC004.3 Section 6.2.2 (particle/m²) |                    | Test For Sorbency Capacity & Rate IEST-RP-C004.3 Section 8.1 |                               |  |                               |                                       |                                    |
|-----------------------------------|------------------------|------------------------|------------------------------|-------------------------|-------------------------|------------------------|--|--------------------|--------------------|---|--------------------|--|-------------------------------|--|-------------------------------|---------------------------------------|------------------------------------|
| lverage                           | Lower<br>SPEC<br>Limit | Upper<br>SPEC<br>Limit | Thick-<br>ness<br>Average    | Thick-<br>ness<br>Lower | Thick-<br>ness<br>Upper | >0.50<br>µm<br>Average | >0.50<br>µm<br>SPEC  | >5.0 µm<br>Average | >5.0<br>µm<br>SPEC | >100<br>µm<br>Average                                       | >100<br>µm<br>SPEC | Extrinsic<br>Capacity<br>(ml/m²)<br>Average                  | Extrinsic<br>Capacity<br>SPEC | intrinsic<br>Capacity<br>(ml/g)<br>Average | Intrinsic<br>Capacity<br>SPEC | Sorptive<br>Rate<br>(Sec.)<br>Average | Sorptive<br>Rate<br>(Sec.)<br>SPEC |
| 140                               | 135                    | 145                    | 0.45                         | 0.40                    | 0.50                    | 4.2                    | < 11.0   | 0.6                | < 0.8              | 104   | <4 00              | 418  | > 400                         | 3.09                                       | >2.8                          | < 1                                   | < 1                                |

|                        | (g/                 | ort Term Ex<br>m²)<br>1.3 Section |             |                            | Specific Extractable lons (ug/g or ppm) IEST-RP-C004.3 Section 7.2.2.1B |                              |                                     |                                |  |   |  |                                |                             |  |
|------------------------|---------------------|-----------------------------------|-------------|----------------------------|---|------------------------------|-------------------------------------|--------------------------------|--|---|--|--------------------------------|-----------------------------|--|
| DI<br>Water<br>Average | DI<br>Water<br>SPEC | IPA<br>Average                    | IPA<br>SPEC | Sodium<br>(Na*)<br>Average | Sodium<br>(Na <sup>+</sup> )<br>SPEC                                    | Potassium<br>(K*)<br>Average | Potassium<br>(K <sup>+</sup> ) SPEC | Calcium<br>(Ca²+)<br>. Average | Calcium<br>(Ca <sup>2+</sup> )<br>SPEC | Chloride<br>(Cl <sup>-</sup> )<br>Average | Chloride<br>(Cl <sup>-</sup> )<br>SPEC | Magnesium<br>(Mg²+)<br>Average | Magnesium<br>(Mg²+)<br>SPEC |  |
| 0.0041                 | < 0.01              | 0.017                             | < 0.04      | 0.13                       | < 0.20  | 0.09                         | < 0.10                              | 0.08                           | < 0.20                                 | 0.08                                      | < 0.10                                 | 0.09                           | < 0.10                      |  |

## **Product Cleanliness Specifications**

The raw materials used in the production of this finished product are compliant with IEST-RP-CC004.3 and in accordance with Teknipure specifications.

## **Product Packaging Specifications**

The packaging materials, method & environment of this finished product are in accordance with Teknipure specifications.

## Shelf Life

Sterile product is marked with an expiration date three (3) years from date of manufacture.

Bill Tested By: (Production Technician) Date of Manufacture: Apr. 21, 2023

