Title	Teknipure C of C
Document Number	FM-8.2.5.1
Revision Date	February 20, 2022

Certificate of Conformance

Wiper Code: TC2PU2-6500 LOT No: 527181-150223

Basis Weight (g/m²) ASTM D3776			Thickness (mm) ASTM D1777-96			Orbital Shake Test for Particles IEST-RP-CC004.3 Section 6.1.4 (x10 ⁶ particle/m ²)			Fiber/Particles IEST-RP-CC004.3 Section 6.2.2 (particle/m²)		Test For Sorbency Capacity & Rate IEST-RP-C004.3 Section 8.1						
Average	Lower SPEC Limit	Upper SPEC Limit	Thick- ness Average	Thick- ness Lower	Thick- ness Upper	>0.50 µm Average	>0.50 µm SPEC	>5.0 µm Average	>5.0 µm SPEC	>100 µm Average	>100 µm SPEC	Extrinsic Capacity (ml/m²) Average	Extrinsic Capacity SPEC	Intrinsic Capacity (mI/g) Average	Intrinsic Capacity SPEC	Sorptive Rate (Sec.) Average	Sorptive Rate (Sec.) SPEC
140	135	142	0.45	0.43	0.48	12	<15	4	<5	1025	<1200	421	>400	3.10	>2.8	<1	<1

	(g/	ort Term Ext m²) I.3 Section			Specific Extractable lons (ug/g or ppm) IEST-RP-C004.3 Section 7.2.2.1B								
DI Water Average	DI Water SPEC	IPA Average	IPA SPEC	Sodium (Na ⁺) Average	Sodium (Na ⁺) SPEC	Potassium (K ⁺) Average	Potassium (K ⁺) SPEC	Calcium (Ca ²⁺) Average	Calcium (Ca ²⁺) SPEC	Chloride (Cl') Average	Chloride (Cl ⁻) SPEC	Magnesium (Mg ²⁺) Average	Magnesium (Mg ²⁺) SPEC
-	-	-	-	0.01	<0.02	0.006	<0.01	0.012	<0.02	0.010	<0.02	0.012	<0.02

Product Cleanliness Specifications

The raw materials used in the production of this finished product are compliant with IEST-RP-CC004.3 and in accordance with Teknipure specifications.

Product Packaging Specifications

The packaging materials, method & environment of this finished product are in accordance with Teknipure specifications.

Shelf Life

Sterile product is marked with an expiration date three (3) years from date of manufacture.

ested By: (Production Technician) 张志馨 Inspected By: (Quality) 王雪艳 Name (printed): 王雪艳 Date of Manufacture: Feb.15.2023







