

Title	Teknipure C of C
Document Number	FM-8.2.5.2
Revision Date	October 18, 2023

Certificate of Conformance

Wiper Code: TZ1MFB-99

LOT No: 527346-261023

Basis Weight (g/m ²) ASTM D3776		Thickness (mm) ASTM D1777-96		Orbital Shake Test for Particles IEST-RP-CC004.3 Section 6.1.4 (x10 ⁵ particle/m ²)		Fiber/Particles IEST-RP-CC004.3 Section 6.2.2 (particle/m ²)		Test For Sorbency Capacity & Rate IEST-RP-C004.3 Section 8.1									
Average	Lower SPEC Limit	Upper SPEC Limit	Thickness Average	Thickness Lower	Thickness Upper	>0.50 µm Average	>0.50 µm SPEC	>5.0 µm Average	>5.0 µm SPEC	>100 µm Average	>100 µm SPEC	Extrinsic Capacity (ml/m ²) Average	Extrinsic Capacity SPEC	Intrinsic Capacity (ml/g) Average	Intrinsic Capacity SPEC	Sorbent Rate (Sec.) Average	Sorbent Rate (Sec.) SPEC
80	75	85	0.25	0.20	0.30	44.5	< 60.0	0.21	< 0.26	173	< 3500	335	>260	3.75	>3.5	< 1	< 1

Extractables - Short Term Extraction (g/m ²) IEST-RP-CC004.3 Section 7.1.2				Specific Extractable Ions (µg/g or ppm) IEST-RP-C004.3 Section 7.2.2.1B			
DI Water Average	DI Water SPEC	IPA Average	IPA SPEC	Sodium (Na ⁺) Average	Sodium (Na ⁺) SPEC	Potassium (K ⁺) Average	Potassium (K ⁺) SPEC
0.017	< 0.03	0.331	< 0.05	15.9	< 50.0	14.2	< 30.0

Product Cleanliness Specifications
The raw materials used in the production of this finished product are compliant with IEST-RP-CC004.3 and in accordance with Teknipure specifications.

Product Packaging Specifications
The packaging materials, method & environment of this finished product are in accordance with Teknipure specifications.

Shelf Life
Sterile product is marked with an expiration date three (3) years from date of manufacture.

Tested By: (Production Technician) B111
 Inspected By: (Quality) MAM
 Name (printed): B111
 Date of Manufacture: Oct. 26, 2023



Toll Free: 844.309.2376 Quality@Teknipure.com www.Teknipure.com