

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard Issue date: 4/25/2023 Revision date: 4/18/2025 Supersedes: 4/25/2023 Version: 2.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture

Trade name : TEKNIPURE 91-100% Isopropyl Alcohol Cleaning Wipes

1.2. Other means of identification

Synonyms/Product Numbers : Product Numbers: TS1MPI100-911, TS1MP91-911, TS1PC96C-69, TS3PBI100-99,

TS3PBI100R-99, TS3PBI100G-99, TS3PBE100S-99, TS2PUI100-44, TS2PUI100R-44, TS2PUI100Z-44, TS2PUI100-99, TS2PUI100Z-99, TS2PUI100P-99, TS2PUI100R-99, TS2PUI100G-99, TS2PUI100G-99, TS2PUI109G-99, TS2PUI10

TS2MWI100Z-99. TS1MFI100-99

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Technical cleaning

Restrictions on use : Professional uses,Industrial uses

1.4. Supplier's details

Teknipure 2150 W. Broadway Rd. Suite 104 Mesa, AZ 85202 T +1 (480) 821-3182 info@teknipure.com

1.5. Emergency phone number

Emergency number : (Chemical Spills, Leaks, Fire, Exposure or Accident only)

VelocityEHS 1-800-255-3924 (in the US & Canada)

+1-813-248-0585 (Outside the US)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquid, Category 2

Serious eye damage/eye irritation, Category 2

Hall

Highly flammable liquid and vapor.

Causes serious eye irritation.

Specific target organ toxicity – Single exposure, Category 3, Narcosis

Hall

May cause drowsiness or dizziness.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 - Keep container tightly closed.

P243 - Take action to prevent static discharges.

P261 - Avoid breathing vapors.

P264 - Wash hands thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear eye protection.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P312 - Call a POISON CENTER, a doctor if you feel unwell.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Get medical advice or attention.

P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO2), dry extinguishing

powder to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of to an approved waste disposal plant to hazardous or special waste collection

point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

Other hazards which do not result in classification : None known.

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Isopropanol	CAS-No.: 67-63-0	91 – 100
Water	CAS-No.: 7732-18-5	0 – 9

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Move the affected person to fresh air. Get medical attention if symptoms occur.

First-aid measures after skin contact : No first aid should be needed.

4/18/2025 (Revision date) EN (English US) 2/12

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Ingestion is unlikely for solid products. No first aid is required for small amounts transferred from

hands to mouth.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects : May cause drowsiness or dizziness. Causes serious eye irritation.

Inhalation : May cause minor irritation to the respiratory tract and to other mucous membranes. May cause

drowsiness or dizziness.

Skin : May cause slight irritation to the skin.

Eyes : May cause moderate irritation, including burning sensation, tearing, redness or swelling.

Ingestion : May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic symptoms : None known.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Not required.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Alcohol-resistant foam. CO2, powder or water spray.

Unsuitable extinguishing media : None.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapour.

Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Cool down the containers exposed to heat with a water spray.

Protection during firefighting : Do not attempt to take action without suitable protective equipment.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Wear suitable protective clothing. Ventilate area. Eliminate all ignition sources.

For non-emergency personnel

Emergency procedures : Keep unnecessary and unprotected personnel away from the spillage.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Environmental precautions : Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams.

Methods for cleaning up : Do not re-use towelette. Pick up wipe and place into a container for disposal. Take up liquid spill

into absorbent material.

Other information : Place in a suitable container for disposal in accordance with the waste regulations (see Section

13).

4/18/2025 (Revision date) EN (English US) 3/12

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Refer to protective measures listed in Sections 7 and 8

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Use only outdoors or in a well-ventilated area. Avoid breathing vapors. Wear personal protective

equipment. Avoid contact with eyes, skin and clothing. Wash hands with water and soap. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Empty containers retain product residue and can be hazardous. Do not re-use empty containers.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep away from

heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store product

sealed in the original container, away from heat and out of direct sunlight.

Incompatible products : Strong oxidizers.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Isopropanol (67-63-0)		
USA - ACGIH - Occupational Exposure Limits		
Local name	2-Propanol	
ACGIH OEL TWA	491 mg/m³	
	200 ppm	
ACGIH OEL STEL	984 mg/m³	
	400 ppm	
Remark (ACGIH)	TLV® Basis: Eye & URT irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI	
Regulatory reference	ACGIH 2022	
USA - ACGIH - Biological Exposure Indices		
Local name	2-Propanol	
BEI (BLV)	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B, Ns	
Regulatory reference	ACGIH 2025	
USA - OSHA - Occupational Exposure Limits		
Local name	Isopropyl alcohol	
OSHA PEL (TWA)	980 mg/m³	
	400 ppm	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

8.2. Appropriate engineering controls

Appropriate engineering controls : Use with adequate general or local exhaust ventilation to maintain exposure levels below the

occupational exposure limits. Assess the risk of potentially explosive atmospheres and the need

for explosion-proof equipment.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection:

In case of repeated or prolonged contact wear gloves. Chemically resistant protective gloves. Consult glove manufacturer's product information on material suitability and material thickness.

Eye protection:

Avoid contact with eyes. Safety glasses with side shields. If there is a risk of liquid being splashed: Splash goggles

Skin and body protection:

None under normal conditions

Respiratory protection:

In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid

Appearance : Clear liquid on a white towelette.

Color : Colorless

Odor : mild Alcohol odour
Odor threshold : No data available
pH : No data available

Melting point : -121 °F (-85°C) (isopropanol)

Freezing point : No data available

Boiling point : $180 \, ^{\circ}\text{F} \, (82 \, ^{\circ}\text{C}) \, (isopropanol)$ Flash point : $54 \, ^{\circ}\text{F} \, (12 \, ^{\circ}\text{C}) \, (isopropanol)$

Flammability (solid, gas) : Flammable liquid.

Vapor pressure : 32.25 mm Hg @ 20°C (isopropanol)

Relative vapor density at 20°C : 2.1 (isopropanol)

Relative density : 0.78

Solubility : Soluble in water.

Partition coefficient n-octanol/water (Log Pow) : No data available

Auto-ignition temperature : > 662 °F (>350°C)

Decomposition temperature : No data available

Viscosity, kinematic : No data available

Explosion limits : Lower explosion limit: 2 vol %

Upper explosion limit: 12.7 vol %

Explosive properties : None. Oxidizing properties : None.

Particle characteristics : No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

VOC content : 6.551 lb/gal

4/18/2025 (Revision date) EN (English US) 5/12

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Strong oxidizers. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Isopropanol (67-63-0)		
LD50 oral rat	5840 mg/kg Source: ECHA	
LD50 oral	4384 mg/kg	
LD50 dermal rabbit	12800 mg/kg Source: ECHA	
LD50 dermal	12870 mg/kg	
LC50 Inhalation - Rat [ppm]	1666.66 ppm/1h	

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

IS	opi	op	anol	(67-	63- 0))

IARC group 3 - Not classifiable

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

Isopropanol (67-63-0)

STOT-single exposure May cause drowsiness or dizziness.

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

Symptoms/effects : May cause drowsiness or dizziness. Causes serious eye irritation.

Inhalation : May cause minor irritation to the respiratory tract and to other mucous membranes. May cause

drowsiness or dizziness.

Skin : May cause slight irritation to the skin.

Eyes : May cause moderate irritation, including burning sensation, tearing, redness or swelling.

Ingestion : May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic symptoms : None known.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse

effects in the environment. An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Hazardous to the aquatic environment, short–term

(acute)

Not classified

Hazardous to the aquatic environment, long–term $% \left(-1\right) =-1$

(chronic)

: Not classified

Isopropanol (67-63-0)		
LC50 - Fish [1]	10000 mg/l Test organisms (species): Pimephales promelas	
EC50 - Crustacea [1]	1000 mg/l	
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas	
ErC50 algae	1000 mg/l	
NOEC chronic crustacea	100 mg/l	

12.2. Persistence and degradability

TEKNIPURE 90-100% Isopropyl Alcohol Cleaning Wipes		
Persistence and degradability	Not rapidly degradable	
Isopropanol (67-63-0)		
Persistence and degradability	Readily biodegradable.	
Chemical oxygen demand (COD)	2.23 g O ₂ /g substance	
Water (7732-18-5)		
Persistence and degradability	Not applicable.	

12.3. Bioaccumulative potential

Isopropanol (67-63-0)	
BCF - Fish [1] 3	
Partition coefficient n-octanol/water (Log Pow)	0.05 Source: ICSC
Partition coefficient n-octanol/water (Log Kow)	0.05

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

12.4. Mobility in soil

Isopropanol	(67-63-0)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)

1.5

12.5. Other adverse effects

Ozone : Not classified

Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Dispose of in accordance with applicable federal, state, and local regulations.

Waste treatment methods : Chemical waste generators must determine whether a discarded chemical is classified as a

hazardous waste.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
UN3175	UN3175	3175	3175
14.2. Proper Shipping Name			
Solids containing flammable liquid, n.o.s. (Propan-2-ol, isopropyl alcohol, isopropanol)	SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Propan-2-ol, isopropyl alcohol, isopropanol)	SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (propan-2-ol)	Solids containing flammable liquid, n.o.s. (propan-2-ol)
14.3. Transport hazard class(es	5)		
4.1	4.1	4.1	4.1
FLAMABLE SOLD			
14.4. Packing group			
II	II	II	II
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available	ple		

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

UN-No. (DOT) : UN3175

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

DOT Special Provisions (49 CFR 172.102)

: 47 - Mixtures of solids that are not subject to this subchapter and flammable liquids may be transported under this entry without first applying the classification criteria of Division 4.1, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Except when the liquids are fully absorbed in solid material contained in sealed bags, each packaging must correspond to a design type that has passed a leakproofness test at the Packing Group II level. Small inner packaging consisting of sealed packets containing less than 10 mL of a Class 3 liquid in Packing Group II or III absorbed into a solid material are not subject to this subchapter provided there is no free liquid in the packet. IB6 - Authorized IBCs: Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2). Additional Requirement: Composite IBCs 11HZ2 and 21HZ2 may not be used when the hazardous materials being transported may become liquid during transport. IP2 - When IBCs other than metal or rigid plastics IBCs are used, they must be offered for transportation in a closed freight container or a closed transport vehicle.

T3 - 2.65 178.274(d)(2) Normal........... 178.275(d)(2)

TP33 - The portable tank instruction assigned for this substance applies for granular and powdered solids and for solids which are filled and discharged at temperatures above their melting point which are cooled and transported as a solid mass. Solid substances transported or offered for transport above their melting point are authorized for transportation in portable tanks conforming to the provisions of portable tank instruction T4 for solid substances of packing group III or T7 for solid substances of packing group II, unless a tank with more stringent requirements for minimum shell thickness, maximum allowable working pressure, pressure-relief devices or bottom outlets are assigned in which case the more stringent tank instruction and special provisions shall apply. Filling limits must be in accordance with portable tank special provision TP3. Solids meeting the definition of an elevated temperature material must be transported in accordance with the applicable requirements of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx) : 151
DOT Packaging Non Bulk (49 CFR 173.xxx) : 212
DOT Packaging Bulk (49 CFR 173.xxx) : 240
DOT Quantity Limitations Passenger aircraft/rail (49 : 15 kg

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

DOT Vessel Stowage Location

: 50 kg

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

TDG

UN-No. (TDG) : UN3175

4/18/2025 (Revision date) EN (English US) 9/12

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

TDG Special Provisions

: 16 - 1) The technical name of the most dangerous substance related to the primary class must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(i)(A) of Part 3, Documentation. The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4. Dangerous Goods Safety Marks. 2) subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical: a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. An example in Canada is the "Food and Drugs Act",56 - When solids that are not dangerous goods and liquids included in Class 3, Flammable Liquids, are in a mixture, the mixture may be handled, offered for transport or transported under this shipping name without the tests and criteria for including substances in Class 4.1, Flammable Solids, first being applied, if a) there is no free liquid visible at the time the mixture is loaded into a means of containment or at the time the means of containment is closed; and b) each means of containment is leakproof.

Explosive Limit and Limited Quantity Index : 1 kg
Excepted quantities (TDG) : E2
Passenger Carrying Road Vehicle or Passenger : 15 kg

Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number : 133

IMDG

Special provision (IMDG) : 216, 274 Limited quantities (IMDG) : 1 kg Excepted quantities (IMDG) : E2 : P002 Packing instructions (IMDG) Packing provisions (IMDG) : PP9 IBC packing instructions (IMDG) IBC06 IBC special provisions (IMDG) : B21 Tank instructions (IMDG) : T3. BK2 Tank special provisions (IMDG) TP33

EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE

EmS-No. (Spillage) : S-I - SPILLAGE SCHEDULE India - FLAMMABLE SOLIDS (REPACKING POSSIBLE)

Stowage category (IMDG) : E

Properties and observations (IMDG) : Mixtures of non-dangerous solids (such as soil, sand, production materials etc.) and flammable

liquids.

IATA

: A46 Special provision (IATA) : E2 PCA Excepted quantities (IATA) PCA Limited quantities (IATA) : Y441 PCA limited quantity max net quantity (IATA) : 5kg PCA packing instructions (IATA) 445 PCA max net quantity (IATA) 15kg CAO packing instructions (IATA) 448 CAO max net quantity (IATA) 50kg ERG code (IATA) 3L

SECTION 15 Regulatory information

15.1. Federal regulations

TEKNIPURE 90-100% Isopropyl Alcohol Cleaning Wipes

SARA Section 311/312 Hazard Classes Refer to Section 2 for OSHA Hazard Classification.

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Isopropanol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

Water (7732-18-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

TEKNIPURE 90-100% Isopropyl Alcohol Cleaning Wipes

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Listed on Thailand Existing Chemicals Inventory (DIW)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the NCI (Vietnam - National Chemical Inventory)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Water (7732-18-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Isopropanol(67-63-0)	U.S New Jersey - Right to Know Hazardous Substance List

SECTION 16 Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard Revision date : 4/18/2025 Issue date : 4/25/2023

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Full text of hazard	Full text of hazard classes and H-statements	
H225	Highly flammable liquid and vapor	
H319	Causes serious eye irritation	
H336 May cause drowsiness or dizziness		

Safety Data Sheet (SDS), USA

Technipure expressly disclaims all express or implied warranties to merchantability and fitness for a particular purpose with respect to the product or information provided recognized sources. While the information is believed to be accurate, Technipure makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Technipure's control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risk of their use, handling and disposal of the product, or from the publications or use of, or reliance upon, information contained herein. This information relates only to the product designated herein and does not relate to its use in combination with any other material or in any other process